

THIS DRAWING IS COPYRIGHT © ALL RIGHTS RESERVED. NO PART OF THIS DRAWING MAY BE REPRODUCED, STORED IN A RETRIEVAL SYSTEM OR TRANSMITTED IN ANY FORM OR BY ANY MEANS WITHOUT THE PRIOR WRITTEN PERMISSION FROM MCELLIGOTT CONSULTING ENGINEERS LIMITED.

### NOTES

- 01. DO NOT SCALE. USE FIGURED DIMENSIONS ONLY.
- 02. THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL OTHER RELEVANT ARCHITECTURAL AND ENGINEERING DRAWINGS.
- 03. FINAL LOCATION OF MINIPILLARS & DUCTS TO BE AGREED WITH ESB SUPERVISOR PRIOR TO INSTALLATION.

HOUSEING SCHEMES FOR ALL INSTALLATION DETAILS .

- 04. PROVIDE FOR ESB METER CABINET, INTERNAL METER & BRACKETS, SURGE PROTECTION & CABLE TO PUMPING STATION CONTROL PANEL.
- 05. REFER TO ESB PUBLICATION ELECTRICAL SERVICES GUIDE BOOK FOR
- 06. THIS DRAWING SHOULD BE READ IN CONJUNCTION WITH THE NATIONAL CODE
- OF PRACTICE FOR CUSTOMER INTERFACE ISSUED BY ESB. .

  17. THIS PROPOSAL IS SUBJECT TO APPROVAL FROM THE LOCAL AUTHORITY &
- PLANNING PERMISSION
- 08. ALL PUBLIC LIGHTING COLUMNS MUST BE A MINIMUM OF 800mm AWAY FROM THE KERB EDGE.
- 09. THERE SHALL NOT BE ANY MATURE TREE WITHIN 6M HORIZONTAL DISTANCE OF A 6M LIGHTING COLUMN OR WITH 8M HORIZONTAL DISTANCE OF AN 8M COLUMN.
- A UNI EIGHTING COLONIN OR WITH ON HORIZONTAL DISTANCE OF AN ON COLONIN
- 10. WHERE ACCESS TO LIGHTING COLUMNS IS OBSTRUCTED ETC A RAISE & LOWER MID-HINGED TYPE COLUMN SHOULD BE USED.
- 11. THIS IS NOT AN APPROVED PUBLIC LIGHTING DESIGN DRAWING INFORMATION ONLY12. LOCATION OF LIGHTING PILLARS TO BE CONFIRMED ON RECEIPT OF ESB DESIGN
- DRAWING.
- 13. THIS SCHEME WILL BE DIMMED TO 75% OUTPUT BETWEEN MID-NIGHT & 6AM. PHOTOCELLS SHALL HAVE 35/18LUX SWITCH ON/OFF LEVELS.
- 14. DRAWING COMPLETED WITHOUT USE OF TAKING IN CHARGE DRAWING.
  15. ALL WORKS TO BE CARRIED OUT IN ACCORDANCE WITH LOCAL AUTHORITY PUBLIC
- 15. ALL WORKS TO BE CARRIED OUT IN ACCORDANCE WITH LOCAL AUTHORIT LIGHTING GUIDELINES AND SPECIFICATION.

#### LEGEND

COLUMN DETAILS A:

HEIGHT :6m BRACKET LENGTH :POST-TOP

LANTERN TYPE :14W LED

MAKE & MODEL :CU-PHOSCO-P950-28-P4A-730-CA0550-14W

COLUMN DETAILS B: HEIGHT

BRACKET LENGTH :POST-TOP

LANTERN TYPE :7W LED

MAKE & MODEL :CU-PHOSCO-P950-R3A-730-CA0250-7W

OTES:

R&L = RAISE & LOWER MID-HINGED COLUMN TO BE USED IN ALL AREAS A HOIST IS INACCESSIBLE FOR MAINTENCE

C/W BAFFLE = COMPLETE WITH BAFFLE

	D	FOR INFORMATION	RT	тмс	RMC	29/08/2025
	С	FOR INFORMATION	RT	тмс	RMC	09/07/2025
	В	FOR INFORMATION	RT	тмс	RMC	27/06/2025
	А	FOR INFORMATION	RT	тмс	RMC	06/06/2025
	ISSUE	DESCRIPTION	DRN	ORIG	APP	DATE



# CONSULTING ENGINEERS

Unit D4, Riverview Business Park, Nangor Road, Dublin 12 tel: +353 (0)1 426 0099 email:info@mcelligott.ie web: www.mcelligott.ie

CLIENT			
			_

PROJECT

## RATHMULLAN

TITLE

## PUBLIC LIGHTING LAYOUT

SHEET	SCALE	PROJECT No.	DRAWING No.
A1	1:1000	25018	E040